

In re of: Ulf [REDACTED] UPMEYER (UPMEYER=4)

claim, or, if that is not possible, please cancel the claim and notify the undersigned.

REMARKS

The above amendment to the specification is being made to insert reference to the PCT application of which the present case is a U.S. national stage. The above amendments to the claims are being made in order to eliminate multiple dependency and for the purpose of reducing the filing fee. Please enter this amendment prior to calculation of the filing fee in this case.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version with Markings to Show Changes Made."

Favorable consideration is earnestly solicited.

Respectfully submitted,
BROWDY AND NEIMARK, P.L.L.C.
Attorneys for Applicant

By: 

Sheridan Neimark

Registration No. 20,520

SN:wrđ

Telephone No.: (202) 628-5197

Facsimile No.: (202) 737-3528

09944773-090401

VERSION WITH MARKINGS TO SHOW CHANGES MADE

3. (Amended) A shelf stacking machine according to claim 1 ~~or 2~~, characterized in that the fork (1) is provided with prism shaped or circular-arc shaped receptacle sections (a, b, c) for various diameters of the paper reels (P).

4. (Amended) A shelf stacking machine according to ~~any of claims 1 through 3~~claim 1, characterized in that the fork (1) is fixed on a vertical fork frame (9) that is supported with its upper end in a horizontal pivot axis (6) and actuated by the actuator (8) to pivot the fork vertically.

5. (Amended) A shelf stacking machine according to ~~any of claims 1 through 4~~claim 1, characterized in that the fork (1) is suspended with a rotating ring (10) from a lift and drive unit formed by a lifting gear frame (11) and a drive frame (12).

6. (Amended) A shelf stacking machine according to ~~any of claims 1 through 5~~claim 1, characterized in that the fork frame (9) is supported with its pivot axis (6) on a fork framework (13), that this fork framework (13) is fixed at its upper end on the rotating ring (10) and the rotating ring (10) is moveable with a moving device (14) on the drive frame (12) for storing and removing reels.

7. (Amended) A shelf stacking machine according to ~~any of claims 1 through 6~~claim 1, characterized in that the actuator (8), which acts onto the fork frame (9) with a lifting element (8a) that can be moved to and fro, is fixed on the fork framework (13) in the height region of the fork (1).

09914773-090401
F04060-E247660

8. (Amended) A shelf stacking machine according to ~~any of claims 1 through 7~~claim 1, characterized in that the drive frame (12) is held on the lifting gear frame (11) at both ends and the lifting gear frame (11) is supported vertically adjustable with rollers (11a) on the stand (2) of the shelf stacking machine (RFZ).

9. (Amended) A shelf stacking machine according to ~~any of claims 1 through 8~~claim 1, characterized in that the stand (2) of the shelf stacking machine (RFZ) is formed U-shaped and stands with its vertical posts (2a) on motor driven moving devices (3), that the lift and drive units (11, 12) lie between the posts (2a) of the rearranged (2)* and the lifting gear frame (11) is guided with its rollers (11a) vertically adjustable on the posts (2a).

10. (Amended) A shelf stacking machine according to ~~any of claims 1 through 9~~claim 1, characterized in that the shelf stacking machine stand (2) is or can be coupled to a transport vehicle (TW) that moves the shelf stacking machine (RFZ) out of the operating aisle (G).

11. (Amended) A shelf stacking machine according to ~~any of claims 1 through 10~~claim 1, characterized in that one horizontal axis pin (14) is disposed in each of the two posts (2a) of the shelf stacking machine stand (2), that both pins (14) are situated coaxially opposite one another and are grasped by the transport vehicle (TW) for the tilting (pivoting of the shelf stacking machine stand from the vertical position into an inclined position).

0991473-90401
FO4060-EZ4T660

12. (Amended) A shelf stacking machine according to ~~any of claims 1 through 11~~claim 1, characterized in that the transport vehicle (TW) is designed portal-like and incorporates vertically adjustable lifting elements (15) with support rollers (16) to raise the shelf stacking machine (RFZ) out of its drive rail (5) in the warehouse floor or pit.

13. (Amended) A shelf stacking machine according to ~~any of claims 1 through 12~~claim 1, characterized in that the lifting elements (15) of the transport vehicle (TW) are vertically adjustable by means of support rollers, either mechanically, electric motor driven, or hydraulically.

14. (Amended) A shelf stacking machine according to ~~any of claims 1 through 13~~claim 1, characterized in that a cross connection (17) is disposed between the posts (20) of the stand (2) of the shelf stacking machine (RFZ) with a clearance channel (17a) that is pulled down to the warehouse floor (B) for picking up a paper reel (P) from the floor with the fork (1).

15. (Amended) A shelf stacking machine according to ~~any of claims 1 through 14~~claim 1, characterized in that the receptacle (1) is formed by a mandrel, preferably a telescoping mandrel.

16. (Amended) A shelf stacking machine according to ~~any of claims 1 through 15~~claim 1, characterized in that multiple shelf stacking machines (RFZ) that are protected against collision by a safety control means can be moved in the operating aisle (G).

091473.090401